

Geberit Duofix Delta 98cm Frame & Cistern for Wall-Hung WC, Plus Delta30 Chrome Flush Plate

Application Purposes:

- For drywall construction
- For installation in part-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62cm
- For floor constructions 0–20cm

Features:

- WRAS approved
- Self-supporting frame, powder-coated
- Frame with \varnothing 9mm drilling holes for fastening in wood frame construction
- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- Feet adjustable 0–20cm
- Connection bend can be mounted without tools
- Concealed cistern with front actuation, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with EN 14055, Class II
- Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- With conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- Fastening option for electrical connection

Technical Data:

- Maximum operating temperature, water 25 °C
- Flush volume, factory setting 5.8 and 3l
- Flush volume large, adjustment range 4.5 / 6 / 7.5l
- Flush volume small, adjustment range 3–4l

What's Included:

- Delta30 Chrome Flush Plate
- Angle stop valve R 1/2", compatible with MF, with adapter ring
- Protection box for service opening
- 2 distance bolts, 2 wall anchors
- Connection set for WC, \varnothing 90mm
- Connection bend 90° made of PE-HD, \varnothing 90mm
- Adaptor socket made of PE-HD, \varnothing 90 / 110mm
- 2 protection plugs, 2 threaded rods M12